

BRAND : "SHOOTFIRE"
ISI MARK : 15683
CAPACITY : 2 KGS
CERTIFICATION MARK : ISI MARK (B.I.S)
OPERATING TEMP. : -20°C - +55°C
OPERATING PRESSURE : 15 KGF/CM²
(@70°F)

MATERIAL

BODY : SEAMLESS ALUMINIUM
VALVE : ALUMINIUM VALVE

"O" RING : RUBBER
PLUNGER : BRASS
SPRING : STEEL
SYPHON TUBE : PVC
HOSE : WIRE BRAIDED TRANSPARENT PVC (B.P - 50 KGF/CM²)
PRESSURE GAUGE : EN APPROVED
CHARGE : DRY CHEMICAL POWDER (ABC) CONFORM TO IS 14609
HANDLE & LEVER : MILD STEEL
NOZZLE : M.S.
ANTICORROSIVE : a) SHOT BLASTING
b) EPOXY POWDER COATING OUT SIDE

PAINTING : P.O. RED AS PER IS: 5 SHADE NO. 538
EMPTY WT. : 0.7 KGS. (APPROX)
FULL WT. : 2.7 KGS (APPROX)
BODI DIA : 110 ± 5 MM
OVERALL HEIGHT : 350±10MM
SHIPPING WEIGHT : 3.15 KGS (APPROX)
FIRE CLASS : A, B
BRACKETS : PROVIDED

PERFORMANCE TEST

HYDRAULIC TEST : 35 KGF/CM² FOR 30 SEC. MIN
THROW OF JET : 3 METER
PERCENTAGE OF DISCHAGE : 90 % MINIMUM WITHIN 16 SECONDS
FIRE RATING : 1A, 8B
BURSTING TEST : 55 KGF/CM²
WORKING PRESSURE : 15 KGF/CM²



SHOOTFIRE DCP (ABC) 2 KG. EXTINGUISHER