

BRAND : "SHOOTFIRE"
ISI MARK : 15683
CAPACITY : 2 KGS
CERTIFICATION MARK : ISI MARK (B.I.S)
OPERATING TEMP. : +5°C - +55°C
OPERATING PRESSURE : 15 KGF/CM²
(@70°F)

MATERIAL

BODY : 1.5 MM THICK ALUMINIUM
VALVE : ALUMINIUM VALVE
"O" RING : RUBBER IS: 5383 TYPE - 3
PLUNGER : BRASS IS: 319 TYPE - 1
SPRING : STEEL IS: 4454 (P-1)
SYPHON TUBE : PLASTIC
HOSE : PVC (B.P.50 KGF/CM²)
PRESSURE GAUGE : EN APPROVED
CHARGE : GAS - FE-36 CLEAN AGENT
HANDLE & LEVER : MILD STEEL
NOZZLE : M.S.
ANTICORROSIVE : a) SHOT BLASTING
b) EPOXY POWDER COATING OUT SIDE
PAINTING : P.O. RED AS PER IS: 5 SHADE NO. 538
EMPTY WT. : 0.8 KGS. (APPROX)
FULL WT. : 2.8 KGS (APPROX)
BODI DIA : 110 ± 5 MM
OVERALL HEIGHT : 350±10MM
SHIPPING WEIGHT : 3.25 KGS (APPROX)
FIRE CLASS : B
BRACKETS : PROVIDED

PERFORMANCE TEST

HYDRAULIC TEST : 35 KGF/CM² FOR 8 SEC. MIN
THROW OF JET : 2 METER
PERCENTAGE OF DISCHAGE : 90 % MINIMUM WITHIN 16 SECONDS
FIRE RATING : 8B
BURSTING TEST : 55 KGF/CM²
WORKING PRESSURE : 15 KGF/CM²

