

BRAND	: "SHOOTFIRE "
ISI MARK	: 15683
CAPACITY	: 4 KGS
CERTIFICATION MARK	: ISI MARK (B.I.S)
OPERATING TEMP.	: +5°C - +55°C
OPERATING PRESSURE (@70°F)	: 15 KGF/CM ²

MATERIAL

BODY	: 1.5 MM THICK ALUMINIUM
VALVE	: ALUMINIUM VALVE
"O" RING	: RUBBER IS: 5383 TYPE - 3
PLUNGER	: BRASS IS: 319 TYPE - 1
SPRING	: STEEL IS: 4454 (P-1)
SYPHON TUBE	: PLASTIC
HOSE	: PVC (B.P.50 KGF/CM ²)
PRESSURE GAUGE	: EN APPROVED
CHARGE	: GAS - FE-36 CLEAN AGENT
HANDLE & LEVER	: MILD STEEL
NOZZLE	: M.S.
ANTICORROSIVE	: a) SHOT BLASTING b) EPOXY POWDER COATING OUT SIDE
PAINTING	: P.O. RED AS PER IS: 5 SHADE NO. 538
EMPTY WT.	: 1.6 KGS. (APPROX)
FULL WT.	: 5.6 KGS (APPROX)
BODI DIA	: 130 ± 5 MM
OVERALL HEIGHT	: 510±10MM
SHIPPING WEIGHT	6.4 KGS (APPROX)
FIRE CLASS	A, B
BRACKETS	PROVIDED

PERFORMANCE TEST

HYDRAULIC TEST	: 35 KGF/CM ² FOR 20 SEC. MIN
THROW OF JET	: 2 METER
PERCENTAGE OF DISCHAGE	: 90 % MINIMUM WITHIN 16 SECONDS
FIRE RATING	: 1A, 13B
BURSTING TEST	: 55 KGF/CM ²
WORKING PRESSURE	15 KGF/CM ²

