

BRAND : "SHOOTFIRE"
ISI MARK : 15683
CAPACITY : 6 LITRES
CERTIFICATION MARK : ISI MARK (B.I.S)
OPERATING TEMP. : +5°C - +55°C
OPERATING PRESSURE : 15 KGF/CM²
(@70°F)

MATERIAL

BODY : SEAMLESS ALUMINIUM
VALVE : ALUMINIUM VALVE

"O" RING : RUBBER
PLUNGER : BRASS
SPRING : STEEL
SYPHON TUBE : PVC
HOSE : WIRE BRAIDED TRANSPARENT PVC (B.P - 50 KGF/CM²)
PRESSURE GAUGE : EN APPROVED
CHARGE : WATER
HANDLE & LEVER : MILD STEEL
NOZZLE : M.S.
ANTICORROSIVE : a) SHOT BLASTING
b) EPOXY POWDER COATING OUT SIDE

PAINTING : P.O. RED AS PER IS: 5 SHADE NO. 538
EMPTY WT. : 1.8 KGS. (APPROX)
FULL WT. : 7.8 KGS (APPROX)
BODI DIA : 160 ± 5 MM
OVERALL HEIGHT : 545±10MM
SHIPPING WEIGHT : 9.2 KGS (APPROX)
FIRE CLASS : A
BRACKETS : PROVIDED

PERFORMANCE TEST

HYDRAULIC TEST : 35 KGF/CM² FOR 20 SEC. MIN
THROW OF JET : 3 METER
PERCENTAGE OF DISCHAGE : 90 % MINIMUM WITHIN 50 SECONDS
FIRE RATING : 2A
BURSTING TEST : 55 KGF/CM²
WORKING PRESSURE : 15 KGF/CM²

