

PORTABLE FIRE EXTINGUISHER

Your First Line of Defence for any fire scenario are Portable Fire Extinguishers. A properly maintained and fully charged fire extinguisher can help minimize damage to your business, injuries to your employees and customers. SHOOTFIRE offers you complete range (DCP, Water Based, Foam Based, Carbon Dioxide and Clean Agent Based) of Mild Steel body extinguishers to aid you in launching an effective fire attack.

SHOOTFIRE extinguishers cover the fire classes A, B and C for all application areas and industries. Manufactured under IS Standards these units ensure long life and peak performance. Our extinguishers are ideally used in Industries, Organisations, Residential Buildings, Homes, Cars, Plants, Terminals and Refineries.

WATER/ FOAM BASED FIRE EXTINGUISHERS

WATER / FOAM BASED STORED PRESSURE TYPE FIRE EXTINGUISHERS

FIRE EXTINGUISHER CAPACITIES	9lt. (Foam)	9lt. (Water)
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	25 sec	60 sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	60 sec.	120 sec
RANGE OF JET	6 mtr.	6 mtr.
EMPTY. WT. (APPROX)	5.35 kg	5.35kg.
FULL WT. (APPROX)	14.35 kg	14.35kg.
FIRE RATING	4A, 89B	3A
WORKING PRESSURE	15 KGF/CM ²	15 KGF/CM ²
HYDRO PRESSURE	35 KGF/CM ²	35 KGF/CM ²
BURSTING PRESSURE	55 KGF/CM ²	55 KGF/CM ²

Approvals:  IS:15683  



CO₂ GAS BASED FIRE EXTINGUISHERS

CO₂ BASED STORED PRESSURE TYPE FIRE EXTINGUISHERS

	2 Kg	3 Kg	4.5 Kg
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 Sec	8 Sec	8 Sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	10 Sec	16 Sec	25 Sec
RANGE OF JET	2 Mtrs	2 Mtrs	2 Mtrs
EMPTY. WT. (APPROX)	6.2 Kg	9.5 Kg	12.5 Kg
FULL WT. (APPROX)	8.2 Kg	12.5 Kg	17 Kg
FIRE RATING	13 B	21 B	21 B
WORKING PRESSURE	60 KGF/CM ²	60 KGF/CM ²	60 KGF/CM ²
HYDRO PRESSURE	250 KGF/CM ²	250 KGF/CM ²	250 KGF/CM ²
BURSTING PRESSURE	600 KGF/CM ²	600 KGF/CM ²	600 KGF/CM ²

Approvals:  IS:15683



* All the Images shown are for illustration purpose only, they are subject to change without any prior notice. Actual product may vary.

* Kindly note, all models are not covered in this information leaflet, we shall be happy to solicit any enquiries on models which are not listed.

CLEAN AGENT GAS BASED FIRE EXTINGUISHERS

CLEAN AGENT STORED PRESSURE TYPE FIRE EXTINGUISHERS

FIRE EXTINGUISHER CAPACITIES	2kg.	4kg.	6kg.	1kg
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	16 sec	20 sec	8 sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	16 sec	20 sec	25 sec	10 sec
RANGE OF JET	2 mtr.	2 mtr.	2 mtr.	1mtr
EMPTY. WT. (APPROX)	2.3 KG	2.75KG	3.3 KG	1.2 kg
FULL WT. (APPROX)	4.3 KG	6.75KG.	9.3 KG.	2.2 kg
FIRE RATING	8B	1A, 34B	21B	8B
WORKING PRESSURE	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²
HYDRO PRESSURE	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²
BURSTING PRESSURE	55KGF/CM ²	55KGF/CM ²	55KGF/CM	55KGF/CM ²



Approval:	EN3.7		IS:15683	EN3.7
GAS: DUPONT™ FE36™ Clean Agent				

POWDER BASED FIRE EXTINGUISHER

ABC STORED PRESSURE TYPE FIRE EXTINGUISHER.

FIRE EXTINGUISHER CAPACITIES	1 KG	2 KG	4 KG	6 KG	9 KG
MINMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 SEC	8 SEC	16 SEC	20 SEC	25 SEC
MAXIMUM PERIOD OF DISCHARGE ATLEAST 90% OF CONTENTS	12 SEC	16 SEC	20 SEC	25 SEC	30 SEC
RANGE OF JET	2 MTR.	3 MTR.	4 MTR.	6 MTR.	7 MTR.
EMPTY. WT. (APPROX)	1 KG	2.3 KG	2.75 KG.	3.3 KG.	5.35KG
FULL WT. (APPROX)	2 KG.	4.3 KG.	6.75KG.	9.3KG.	14.35KG.
FIRE RATING	1A, 8B	1A, 8B	2A, 34B	4A, 55B	6A, 89B
WORKING PRESSURE	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²
HYDRO PRESSURE	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²
BURSTING PRESSURE	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²

Approval:		IS:15683
-----------	---	----------

